



System
zarządzania
ISO 9001:2015

www.tuv.com
ID 9105058465

OXYLINE Sp. z o.o., 95-200 Pabianice, ul. Piłsudskiego 23
Sąd Rejonowy dla Łodzi-Śródmieścia, nr KRS: 0000299083, NIP: PL7692143818, REGON: 100482830
Nr konta: Bank Millennium S.A., 26 1160 2202 0000 0001 0694 2836, Kapitał zakładowy: 2 325 000,00 zł
tel. 42 215 10 68, 42 203 203 5, fax: 42 203 203 1, e-mail: oxyline@oxyline.eu, Internet: www.oxyline.eu

EU DECLARATION OF CONFORMITY

1. Personal protective equipment **XC 210V FFP2 R D**
2. Manufacturer's name and address:
Oxyline Sp. z o.o., ul. Piłsudskiego 23, 95-200 Pabianice, POLAND
3. This declaration of conformity is issued under the sole responsibility of the manufacturer:
Oxyline Sp. z o.o., ul. Piłsudskiego 23, 95-200 Pabianice, POLAND
4. Object of the declaration is the filtering half-mask **XC 210V FFP2 R D** to protect the respiratory system against particles.
5. The object of the declaration described in point 4 is in conformity with the relevant Union harmonisation legislation: **Regulation (EU) 2016/425 of the European Parliament and of the Council of March 9, 2016. on personal protective equipment and repealing Council Directive 89/686 / EEC.**
6. Filtering half-mask XC 210V FFP2 R D meets the requirements of the harmonized standard **EN 149: 2001 + A1: 2009** and meets the requirements of §221 of the Regulation of the Minister of Energy of November 23, 2016 on detailed requirements regarding the operation of underground mining plants: "It is unacceptable to use personal protective equipment as well as work clothing and footwear in an explosive atmosphere that may: 1) be a source of an electric spark or arc caused by static electricity or impact, 2) cause the ignition of an explosive mixture" (Journal of Laws of 2017, item 1118)
7. Notified body **Central Institute for Labor Protection - National Research Institute, ul. Czerniakowska 16, 00-701 Warsaw** - No. 1437 conducted the EU test (module B) and issued EU type examination certificate No. **UE / 198/2019/1437**
8. Where appropriate, PPE is subject to a type-conformity assessment procedure based on quality assurance of the production process (module C2), under the supervision of notified bodies **Central Institute for Labor Protection-National Research Institute, ul. Czerniakowska 16, 00-701 Warsaw** - No. 1437

Signed : **Oxyline Sp. z o.o.**

Pabianice 31 July 2019


Arkadiusz Dziębowski
President

OXYLINE Sp. z o.o.
95-200 Pabianice, ul. Piłsudskiego 23
tel 42 215-10-68, 42 203 203 5
fax 42 203 203 1
NIP 7692143818; Regon 100482830

Data sheet

Filtering half mask: **XC 210 V FFP2 R D**

Certificate: UE/198/2019/1437

Date of issue: 31 July 2019

Catalogue number: XC 210 V FFP2 R D

CE 1437

PURPOSE:

The respirator XC 210 V FFP2 R D is designed to protect respiratory system against harmful effect of dust, solid and liquid aerosols when OEL is $\geq 0,05$ mg/m³ and the concentration of dispersed phase of aerosol does not exceed

10 x OEL (Occupational Exposure Limit),

10 x APF (Assigned Protection Factor),

12 x NPF (Nominal Protection Factor).

The layer of active carbon protects the respiratory tract from the simultaneous irritating effect of aerosols and vapours of organic or in-organic substances with the concentration level lower than the OEL, NPF, APF.

EXAMPLES OF APPLICATION:

Medium toxic solids, asbestos, copper, barium, titanium, vanadium, chromium, manganese, hardwood, coal dust with free silica content higher than 10%, mining industry, chemical industry, metallurgic industry, welding, soldering, respirable dusts. Waste sorting, battery production, painting and interior decorating, wastewater treatment plants.

HOW IT WORKS:

The filtering half mask is composed mostly of the face part made of filtering material and accessories such as headbands, or exhalation valve, depending on the model. When air is drawn in, it passes through the filtration material where it is cleansed before being inhaled. Exhaled air passes through filtration material (in the masks without a valve) or through both the exhalation valve and the filtration material (in models with a valve). The cup of the mask should be well adjusted to the user's face.

DESCRIPTION:

The filtering half mask XC 210 V FFP2 R D is composed of the following elements:

- A multi-layered filtration material: polypropylene
- An internal layer of activated carbon
- A nose clip to shape the half mask at the nose
- Exhalation valve
- Head bands made of braided rubber thread
- Plastic fastenings of the head bands
- Nose seal made of polyurethane foam

The half mask is designed in such a way as to enable easy breathing throughout the work shift. The anatomical shape and the nose clip, as well as the internal sealing foam, make the half mask easy to fit to most face shapes, so that the necessary tightness can be ensured.

REQUIREMENTS:

OXYLINE half masks comply with the following::

- harmonised European standard EN 149:2001+A1:2009 " Respiratory protective devices - Filtering half masks to protect against particles. Requirements, testing, marking ";
- in conformity with the relevant Union harmonisation legislation: Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC (Text with EEA relevance).



CONTRAINDICATIONS:

It does not ensure protection of the respiratory system if there is a lack of oxygen (below 17%). It should not be used in spaces with limited cubic volume, in particular non-ventilated spaces, such as sewers, wells, tanks, etc. The half mask does not provide protection against pollution in the form of gas fumes or mists of substances that are harmful to human health and hazardous to life. Do not use the half mask if the type, characteristics and concentration of the harmful substances are unknown. Do not use the half mask when extinguishing fires. The half mask does not ensure tightness if worn on an unshaven or bearded face.

FUNCTIONAL PARAMETERS OF THE HALF MASK XC 210 V FFP2 R D

| | | |
|--|-------------------------|----------|
| Class (according to EN 149:2001+A1:2009) | FFP2 | |
| Penetration of filtering material by sodium chloride aerosol or oil mist | ≤ 6% | |
| Total leakage | ≤ 8% | |
| Initial inhalation resistance at a flow of 95 l/min | ≤ 240 Pa | |
| Initial exhalation resistance 160 l/min | ≤ 300 Pa | |
| Breathing resistance at the end of clogging test with dolomite dust, at a flow of: | 95 l/min (inhalation)) | ≤ 500 Pa |
| | 160 l/min (exhalation)) | ≤ 300 Pa |

UŻYTKOWANIE I PRZECHOWYWANIE

The half masks should be stored at a temperature of -30°C to +50°C and humidity below 70%. Before the half mask is used, its technical condition should be checked, i.e. whether the elements are not damaged. Damaged or expired half masks must not be used. The half mask should not be folded or bent. In order to ensure the best possible fit on the face, the half masks should be put on and adjusted in the following manner::


1. Before putting on the half mask, form the nose clip by tightening,
2. Place the mask over the face to cover the mouth and the nose;
3. Put the head bands on in such a way as to make the lower band pass around the nape of the neck below the ear, and the upper band pass around the back of the head above the ear; the length of upper and lower band can be adjusted;
4. Further adjust the nose clip to ensure tightness
5. Check that you have the correct mounting. Press your hands and hold the dome of the mask. Exhale energetically; if there is any looseness adjust the position of the dome, the nose clamp or headbands.
6. Shelf life 60 months. The expiry date on the product.



After each use, the mask should be disinfected. This can be done by spraying the mask with liquid designed for disinfecting filtration half masks (1-2 sprays) or cleaning the inside of the half mask with a cloth soaked with pure ethyl alcohol. The half mask can only be used again by the same user. The disinfected half mask must be stored according to storage guidelines. A half mask can be used for longer than eight hours by the same user, provided it hasn't been broken and that it has been disinfected. Over time, breathing resistance in the mask will increase due to the settling of dust. If resistance has grown significantly, the mask should be replaced by a new one. In case of use in an explosive atmosphere, contact Oxyline Sp. z o.o.

ADJUSTING THE HEAD BANDS:

To adjust the head bands, put the strap between the plastic hooks as shown in illustration 2. Looping it a number of times between the hooks will shorten the band and tighten the mask when it is put on. In order to extend the length again just take the band off the hooks. For more precise adjustment of the head band, wind or unwind the band on/off each hook, as shown in illustration 3.



Notified body Central Institute for Labor Protection - National Research Institute, ul. Czerniakowska 16, 00-701 Warsaw, - No. 1437.

Data sheet. 30.07.2021.

Oxyline Sp. z o.o.

95-200 Pabianice, ul. Piłsudskiego 23

tel.: 42 215 10 68 fax: 42 2032031

www.oxyline.eu email: oxyline@oxyline.eu